

NOTES:

ELECTRICAL:


1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

MECHANICAL:

1. HOUSING MATERIAL:PBT;
2. PANEL FRAME:CARBON STEEL, POWDER, COATING IN BLACK COLOR, Spcc1.5mm;
3. PCB MATERIAL:FR-4 T=1.6mm ;
4. IDC MATERIAL:PC , CONTACT:PHOSPHOR BRONZE; WITH NICKEL PATING;
5. SHIELD MATERIAL: STAINLESS STEEL, T=0.2mm
6. RJ45 JACK LIFE:750 TIMES MIN;
7. IDC LIFE:200 TIMES MIN;
8. WIRE:AWG 22-26;

					<div>COPA®</div>						
					Material					Item No.	17680
SYM	Number	Bill No. of Alteration	Signature	Date	Angles Projection		Size	Scale	Unit	DWG No.	
Drawn	Ding jian bo	2016.1.13	Tolerance				A4	X:1	mm	Part Name	8Ports Cat.6 STP Patch Panel
Checked	Ge pei jun	2016.1.13	0.00-20.00 ±0.10 20.00-50.00 ±0.15 50.00-100.00 ±0.20 100.00- Angle ±0.25 ±30'							ERP	10100121
Approved	Wang wei jun	2016.1.13								Part No.	
					Sheet	1 OF 1	Version: A/0				